Please pe a plus sign (+) inside this box [+] Patent and Trademark Office: U.S. Department of Commerce 00010 TO 10/95 U.S. Department of Commerce **Application Number** 10/622,105 Patent and Trademark Office Filing Date 07/17/2003 First Named Inventor Parminder S. Sangha TRANSMITTAL FORM Group Art Unit 2834 (to be used for all correspondence after initial filing) **Examiner Name** Total Number of pages in this Submission Attorney Docket Number 248-00284

ENCLOSURES (check all that apply)				
☐ Fee Transmittal Form ☐ Fee Attached	☐ Assignment Papers (for an Application)	☐ After Allowance Communication To Group		
☐ Amendment/Response ☐ After final	☐ Drawing(s)	<ul> <li>Appeal Communication to Board Of Appeals and Interferences</li> <li>Appeal Communication to Group ( Appeal Notice, Brief, Reply Brief)</li> </ul>		
☐ Extension of Time Request	☐ Licensing-related Papers  · ☐ Petition Checklist and			
☐ Express Abandonment Request	Accompanying Petition			
☐ Information Disclosure Statement/PTO-1449	☐ To Convert a Provisional Application	☐ Proprietary Information		
☑ Certified Copy of Priority	☐ Power of Attorney, Revocation, Change of	☐ Status Letter		
Document(s)  ☐ Response to Missing Parts/	Correspondence Address  ☐ Terminal Disclaimer	✓ Additional Enclosure(s)     (Please identify below)		
Incomplete Application □Response to Missing Parts Under 37 1.52 or 1.53		Return receipt postcard		
	Remarks			
	Temans			
	URE OF APPLICANT, ATTORNEY, O	R AGENT		
Firm JOSEPH J. JC	CHMAN (Reg. No. 25,058)	,		
	EALES, STARKE & SAWALL, LLP	WI 53202		
Signature but	Johnner .			
Date September 9,	2003			
CERTIFICATE OF MAILING				
I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, DC 20231 on this date:				
September 9, 2003				
Typed or printed name Barbara A. Johnson				
Signature Date 9/9/2003				



## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application Of:	)
PARMINDER S. SANGHA	)
Application No.: 10/622,105	)
Filed: 07/17/2003	)
Group Art Unit: 2834	)
Examiner:	)
HEATING SYSTEM	)

# TRANSMISSION OF PRIORITY DOCUMENT

COMMISSIONER FOR PATENTS Washington, D.C. 20231

Sir:

Enclosed is a certified copy of the priority document identified in the formal papers of this application as filed.

The claim for priority made in the formal papers is reiterated.

Acknowledgement of the receipt of this certified copy in the next Patent Office correspondence is respectfully requested.

Respectfully submitted,

ANDRUS, SCEALES, STARKE & SAWALL, LLP

Joseph J. Jochman Reg. No. 25,058

Andrus, Sceales, Starke & Sawall, LLP 100 East Wisconsin Avenue, St. 1100 Milwaukee, WI 53202 (414) 271-7590

Attorney Docket No: 248-00284

	,		Control of the second of the s
		·	
			•
			•
		,	







The Patent Office Concept House Cardiff Road Newport South Wales NP10 800

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed Qbehan

Dated 24 July 2003

		·
		-
		•
	•	•

Patents Form 1/77 K
Patents Act 1977 (Rule 16)

Patents Act 1977 | 17 JUL 2002

Patent Softice Office

18JUL02 F734341-3 D00355 -01/7700 0.00-0216713.8

Request for grant of a patent

this request? (Answer 'Yes' if:

applicant, or

See note (d))

a) any applicant named in part 3 is not an inventor, orb) there is an inventor who is not named as an

c) any named applicant is a corporate body.

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road Newport South Wales

NP10 8QQ 1. Your reference R071502PGB 2. Patent application number 0216713.8 (The Patent Office will fill in this part) 3. Full name, address and postcode of the or of Lucas Industries Limited each applicant (underline all surnames) Stratford Road, Solihull West Midlands B90 4LA England Patents ADP number (if you know it) 576694002 If the applicant is a corporate body, give the **England** country/state of its incorporation Title of the invention HEATING SYSTEM 5. Name of your agent (if you have one) Marks & Clerk Alpha Tower "Address for service" in the United Kingdom Suffolk Street Queensway to which all correspondence should be sent (including the postcode) Birmingham B1 1TT England Patents ADP number (if you know it) 18002 6. If you are declaring priority from one or more Country Priority application number Date of filing earlier patent applications, give the country (if you know it) (day / month / year) and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number 7. If this application is divided or otherwise Date of filing Number of earlier application derived from an earlier UK application, (day / month / year) give the number and the filing date of the earlier application 8. Is a statement of inventorship and of right Yes to grant of a patent required in support of

#### Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim (s)

Abstract

Drawing (s)

+ 1 2

If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signatur

Date

165ULY 2002

Name and daytime telephone number of person to contact in the United Kingdom

Joanne S POPLE

0121 643 5881

### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

#### Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

## **HEATING SYSTEM**

The present invention relates to a heating system and particularly, but not exclusively, to a system for heating fluid used for cooling and/or lubricating a motor or the like. The invention finds particular application in heating the hydraulic fluid used in electro-hydraulic actuators to cool and/or lubricate the motor which drives the hydraulic pump.

Aircraft often employ electro-hydraulic actuators as control systems for the primary flight control surfaces of the aircraft, for example the ailerons, spoilers, elevators and rudder. Such electro-hydraulic actuators generally include an actuator for moving the flight control surfaces under the control of an hydraulic pump. Conventionally, the hydraulic pump is driven by an electric motor to which it is directly mounted.

15

20

10

5

It is known to use the hydraulic fluid from the pump as a lubricant and coolant for the electric motor. Specifically, the hydraulic fluid from the pump is allowed to flow into the motor and through the air gap between the rotor and the stator of the motor. The fluid exits the motor at the end remote from the hydraulic pump and is directed back into the hydraulic system. The fluid flowing through the motor lubricates the motor bearings and provides a cooling effect on the motor itself.

Typically, the hydraulic fluid which is used is highly corrosive, for example

Type 4 phosphate ester. It is therefore necessary to isolate the stator windings from the fluid. A sleeve is therefore provided in the air gap which lines the stator bore and isolates the coil windings from the hydraulic fluid.

The motor is required to operate over a temperature range of between approximately -55°C and 120°C. As the temperature of the hydraulic fluid decreases, its viscosity increases such that at the lower end of the operating temperature range, the viscosity of the hydraulic fluid can impede or prevent the motor from starting. Clearly, this can be a problem where the electro-hydraulic actuator is used on aircraft intended to operate in regions having an extremely cold climate and can be highly dangerous if the motor fails to start whilst the aircraft is in flight at an altitude where the temperature is extremely low.

5

10 US 4, 922, 119 discloses a starting system for an aircraft propulsion engine. An electric motor is mounted within a case which contains hydraulic fluid used by first and second hydraulic units as part of a constant speed drive transmission. The electric motor provides some heating for the hydraulic fluid but this heating exists only after power up of the motor and is therefore of no assistance in starting the motor itself.

It would be advantageous to provide a method and/or apparatus which addresses the problem of starting the electric motor at very low temperatures.

- According to one aspect of the present invention, therefore, there is provided an electric motor arranged for passing therethrough a supply of fluid for cooling and/or lubricating said motor, the motor being provided with heating means for heating the fluid when the fluid enters the motor.
- Advantageously, the motor is arranged such that the fluid flows through an annular gap between the rotor and the stator of the motor.

Conveniently, means are provided for isolating the stator windings from the fluid.

Preferably, the heating means is arranged, in use, to raise the temperature of the fluid above -50°C. More preferably, the heating means is arranged, in use, to raise the temperature of the fluid to a value no less than -40°C.

5

Preferably a thermostatic switch is used in association with the heating means.

Advantageously, the heating means is arranged such that it is not in contact with the fluid.

10

Preferably, the heating means comprises an annular heating element.

The heating element may be mounted to the motor radially outwardly or behind the motor bearings.

15

Preferably, the heating element is mounted close to or adjacent to a region of the motor at which the fluid enters the motor. More preferably, the heating element is mounted to the bearing block of the motor.

The motor may be associated with an hydraulic pump and the fluid may comprise hydraulic fluid supplied by said hydraulic pump.

In one embodiment, the motor is used to drive an hydraulic pump forming part of an electro-hydraulic actuator.

25

The present invention will now be described, by way of example only, with reference to the accompanying drawing which illustrates a section through a preferred form of motor according to the invention.

Referring to the drawing, a motor according to the invention is shown generally at 10. The motor 10 comprises a rotor 12, rotatably mounted within a casing 14 of the motor, and a stator 16 including a plurality of windings 16a and a magnetic core 16b.

5

The rotor 12 is radially spaced from the stator within the housing 14 such that an annular gap 18 exists therebetween. The rotor 12 rotates within the housing 14 on bearings 20 which are mounted within a so-called bearing block 21.

In the illustrated embodiment, the motor is associated with an hydraulic pump (not shown) which is connected to the motor at one end E thereof and driven by the rotor 12. The hydraulic pump may be arranged to control an hydraulic actuator by means of the application of hydraulic fluid thereto.

In order to provide a cooling effect on the rotor 12 and stator 16 of the motor and to lubricate the bearings 20 within the bearing block 21, the hydraulic pump is arranged to provide a source of hydraulic fluid which is applied to, and flows through, a fluid path, illustrated by the arrows in the drawing, defined within the motor.

20

25

Specifically, the fluid flows into the bearing block 21 from the pump to provide lubrication for the bearings 20 and then through the annular gap 18 defined between the rotor 12 and the stator 16 of the motor. A drain hole (not shown) is provided in the casing 14 of the motor at a second end D thereof for recycling back to the hydraulic pump or to the hydraulic system to which the pump is connected.

As described above, at temperatures below approximately -40°C, the viscosity of the hydraulic fluid becomes high enough to effect the operation of the motor. In

particular, the starting torque of the motor is insufficient to overcome the viscosity of the hydraulic fluid and, at temperatures below -40°C, it may become difficult or impossible to start the motor.

- The present invention therefore provides heating means, in the form of an annular heating element 22, thermally coupled to the body of the motor. The heating element preferably comprises an electric heater but may conveniently comprise any suitable heating apparatus.
- 10 The heating element 22 is disposed radially outwardly of the bearing block 21 but in close proximity thereto. Preferably, the heating element is mounted directly to the bearing block 21, in good thermal contact therewith. The heating element 22 is physically and/or electrically isolated from the hydraulic fluid flowing through the bearing block 21, in order to reduce or substantially eliminate the likelihood of fire.

Due to good thermal contact with the heating element 22, the main body of the motor, which is closely coupled to the pump, is heated. Thus, fluid within the pump also experiences a temperature rise, resulting in improved pump efficiency at low temperatures.

20

25

The heating element 22 is arranged to raise the temperature of the hydraulic fluid by approximately 15°C, for example from -55°C to approximately -40°C. This relatively small increase in temperature is sufficient to reduce the viscosity of the hydraulic fluid to a level at which it does not affect the operation of the motor.


Owing to the relatively small rise in temperature required, it is envisaged that the heating element 22 may have a power rating of approximately 100 watts. The heating element 22 may be provided with a thermostat which switches on the

heating element 22 at a temperature of between -40°C and -30° C. Heat from the heating element 22 is transmitted through the bearing block 21 and the bearings 20 to the hydraulic fluid so as to provide a good thermal contact therewith.

5

Since the hydraulic fluid is heated on entering the motor, only a relatively low power heating element is necessary and the arrangement avoids the need to heat all of the hydraulic fluid thereby increasing the efficiency of the apparatus.

It will be appreciated that the present invention provides a simple and effective solution to the problem of increased hydraulic fluid viscosity at very low temperatures. The heating element is simple and inexpensive to fit to existing motors and requires very little power.



	•	. •	•	
•				
				• ·